POWER MOULD RELEASE

Rapid Mould Release Agent

Power Construction Chemicals (Pvt. Ltd.)

PRODUCT DESCRIPTION

POWER MOULD RELEASE based on environmentally safe raw materials present an ecological alternative to the mineral-oil-based mould release agents. POWER MOULD RELEASE is harmless to the environment while considerable quantities of mould release oils pollute the environment when decorative, pre-cast concrete sections and concrete sleepers are being casts.

PRIMARY APPLICATION

Can be applied to all commonly use shuttering systems using coated and concrete chipboard, steel, wood, etc.

- A compatibility check shall be made prior to industrial application and ambient conditions may influence the properties of the concrete surface and consumption of the mould release oil.
- May be applied manually with a brush or oil-resistant spraying device.
- Mixing with mineral oil or solvents is not at all environmentally safe.
- Cannot be used for the protection of mixers they may attack lacquer, eastomers or plastic parts in the worst case.
- Dissolve Styropor if applied all-over. Damage to Styrodur (green) will be less severe. If contact with this material cannot be avoided then reduce the quality to be applied.
- Ready-to-use and shall not be diluted with solvents.

SAFETY INFORMATION

Observe local water regulations.

- Avoid open flames.
- Do not smoke.
- Do not inhale spray mist.
- Change product-soaked clothing.

POWER MOULD RELEASE has the following features:

- Simple, reliable and clean mould removal.
- Economical
- A film of the mould release agent temporarily protects metal parts from corrosion and does not corrode
- non-ferrous metals.

Almost complete inhibition of blowhole, pore formation an staining.

Direction for Use

Power Mould release can be applied by brush spray and storage on the prepared surface

PHYSICAL & CHEMICAL PROPERTIES

Appearance: Pale Yellow/Straw Color

Gravity: 0.83 @ 20°C

Temperature limitation: 0°C-60°C

Observe industrial hygiene regulations.

STORAGE

Avoid to place direct to sun light and always store in shady areas.

WARRANTY: The Power Chemicals LLC. ("Power") solely and expressly warrants that its products shall be free from defects in materials and workmanship for 12 months from the date of purchase. Unless authorized in writing by an officer of Power no other representations or statements made by Ultra or its representatives, in writing or orally, shall alter this warranty. POWER MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Power product fails to conform this warranty, Power will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Power does not authorize anyone on its behalf to make any written or oral statements which in any way alter Power installation information or instructions in its product literature or on its packaging labels. Any installation of Power products which fails to conform to such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Power products for the Buyer's intended purposes.

Power Construction Chemicals (Pvt. Ltd.)

www.powerchemicalspk.com | Emial Id: info@powerchemicalspk.com

Office # 10-B, Ziarat Trade Center Tarnol Islamabad-Pakistan